



- A. 14" ON CENTER LAMP SPACING
 - B. CONSTRUCTION: FORMED ALUMINUM
 - C. FINISH: SATIN ANODIZED
 - D. ALL DIMENSIONS ARE NOMINAL.
 - E. LAMP LENGTHS MAY VARY FROM MANUFACTURER.
 - F. PLEASE ALLOW A NOMINAL 4" FOR LAMP OVERHANG.
 - G. SPECIAL LAMP CLIP AND MOUNTING BRACKET REQUIRED FOR LAMP DOWN CONFIGURATION. (MUST BE ORDERED SEPARATELY)
- ORDER: P-2013-01-00

2855NX239 IS COMPATIBLE WITH 2855FX239 LAMP - UP/DOWN SERIES.

^{UL} LISTED
DAMP LOCATION

choose one from each category

ORDERING FORMAT					
SERIES	LAMP CONFIGURATION	LAMP	VOLTAGE	BALLAST	LENGTH
2855 linear fixture	NX2 seamless straight lamp up or down	<input type="checkbox"/> 39 watt compact fluorescent	<input type="checkbox"/> 1 120 volt <input type="checkbox"/> 2 277 volt	<input type="checkbox"/> H high power factor (28" & 14" only) <input type="checkbox"/> E electronic <input type="checkbox"/> D dimming	<input type="checkbox"/> 42" length (3 lamps) <input type="checkbox"/> 28" length (2 lamps) <input type="checkbox"/> 14" length (1 lamp)

JOB NAME: _____

APPROVED FOR FABRICATION: _____

REV.1 6-22-99 DK
REV.2 9-12-00 DK

* ALL DIMENSIONS SHOWN ARE IN INCHES



division of
LIGHTING WORLD INC
1703 VALLEY ROAD
OCEAN NJ 07712
TEL (732) 493-2666
FAX (732) 493-2941

DATE 3-11-97 SCALE NTS DRAWN DK APPROVED NA
SHEET 1 OF 1 DRAWING NUMBER SUBJ 2855NX39 REV.2

THIS DOCUMENT IS THE PROPERTY OF LIGHTING WORLD INC. NO RIGHTS ARE GRANTED FOR REPRODUCTION, DISCLOSURE, OR USE. STANDARD MODIFIED CUSTOM
COPYRIGHT © LIGHTING WORLD INC.